## 29 137

## **GROHTHERM® SMARTCONTROL**

## Pure Frende an Wasser

## DUAL FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

#### STANDARD SPECIFICATION:

- GROHE StarLight®
- GROHE SmartControl®: push for ON-OFF, turn for volume adjustment from EcoJoy™ to Full Flow, exchangeable symbols
- GROHE TurboStat® compact 3/4" cartridge with wax thermo element
- GROHE SafeStop safety button with manual override at 100°F/38°C
- GROHE SafeStop Plus temperature limiter at 115° F/46° C
- · Multiple outlets can be run simultaneously
- 6 1/4" Metal wall escutcheon with GROHE QuickFix®
- 3/8" Thin profile escutcheon
- Wall plate is angle adjustable up to 6°
- · Optional flow reducer for CALGreen compliance included (Note: Cannot be used for shower systems that include tub spout)
- · Built-in check valve with dirt strainer
- Includes icons to customize push buttons: Hand Shower, Showerhead & Bath Filler
- Includes service stops
- Maximum combined flow performance: 7.7gpm (29L/min) @ 43.5psi (3 bar)
- Requires Grohtherm® Rapido® SmartBox (35 601) (sold separately)



#### **PRODUCT FEATURES:**



GROHE StarLight®



GROHE TurboStat®



GROHE QuickFix®

#### **CERTIFICATIONS:**

- Massachusetts Plumbing Board Approved
- CSA B125.1
- ASME A112.18.1

#### **AVAILABLE FINISHES:**

**GROHE StarLight®** 29137000 Chrome

Hard Graphite 29137A00

Polished Nickel 29137BE0 InfinityFinish™

**Brushed Nickel** 29137EN0 InfinityFinish™

Brushed 29137GN0 Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.



## 29 137

## **GROHTHERM® SMARTCONTROL**



# DUAL FUNCTION THERMOSTATIC VALVE TRIM WITH CONTROL MODULE

#### **TECHNICAL DATA:**

Product Height 6-1/4 in

Product Length 1-11/16 in

Product Width 6-1/4 in

